

3W6 SWAMP BUGGY

COMBINING TECHNOLOGY AND TRADITION SINCE 1976



GK 3W6 self-propelled spray buggy has been designed for light-weight, high-flotation applications for both spreading and spraying. The three-wheel stance provides staggered tire spacing to limit ground pressure and compaction.

2020 New Updates and Features:

- A stronger frame, up to 200% stronger in key areas
- Larger, easily accessible hydraulic oil filter
- Increased fuel economy and quieter operation
- Improved front to rear weight balance and improved operator visibility
- Extensive use of aluminum and high strength steel to reduce overall weight
- Pressurized stainless steel wide cab with sound insulation, charcoal air filtration, climate control (A/C, Heat & Defrost), AM/FM stereo radio, CD player and comprehensive digital display cluster
- Improved access to maintenance locations
- Side-by-side radiator assembly with tool free grill removal for easy cleaning
- Improved ground clearance

3W6 Swamp Buggy is powered with a Cummins Stage V, 4.5 liter, 173 HP, 4-cylinder engine which provides 590 feet-lbs. of torque. It's driven by a JCB rear-end that has an outboard planetary, single speed with

internal wet brakes. The chassis features a wheel base of 16 feet and offers 6,000 lbs. payload capacity. It has a dry weight of 11,700 lbs., and can be configured with Tundra Flotation Tires or row crop tires.

This versatile machine spraying/dry-box system is configured with a 600-gallon stainless steel tank with mechanical agitation and 60 feet or 80 feet stainless booms. Dry spreading system comes with a three-ton stainless dry box with dual spinners.



Call for a friendly quote!

503-678-5525

10590 Donald Road NE · Donald, Oregon 97020 FAX 503-678-5693 gksales@gkmachine.com · www.gkmachine.com

3W6 SWAMP BUGGY

COMBINING TECHNOLOGY AND TRADITION SINCE 1976



Specifications:

Product.....3W6 Swamp Buggy
Tractor Weight (lbs.).....11,700 lbs.
Dry Spreader Set-up Weight (lbs.).....13,000 lbs.
Spray Boom Set-up Weight (lbs.).....15,400 lbs.
Tank.....600-gallon stainless steel
Engine.....Cummins 173 HP (Stage V)
Transmission/Drive Speed.....Allison, 0-25 MPH
Suspension.....Air (Front Fork)
Cab....Stainless steel wide cab with charcoal filter and buddy seat
Steering.....Char-Lynn Pressure Sensing Orbitrol
Rear Axle.....Outboard planetary, single speed with internal wet brake
Tires.....66 x 44 x 25 Tundra Flotation Tires
Boom Height.....24 to 72 inches
Crop Clearance.....22.5 inches
Boom Length.....60 to 80 feet
Pump.....Centrifugal Hypro HM1
Spray Control.....Raven Control Systems

Operational Features:

Spray Boom: 60 or 80 feet suspended boom with stainless steel wings
Hydraulic or mechanical breakaway
Up to 12 section product control
Raven and Teejet precision components

Dry Spreader: 3-ton capacity dry box (80 cubic feet) with dual product chains and spinners
120 cubic feet extension with tarp kit
Digital product scale

Tires: Row crop 12.4R46 radial tires
Custom wheels to fit customer supplied tires

Other Options: GK Foam Marking System – 10 & 15 gallon
GK Venturi Chemical Mixing Station
GK Custom Sprayer Trailer
Power Tank Fill
Trailer Hitch



Call for a friendly quote!

503-678-5525

10590 Donald Road NE · Donald, Oregon 97020 FAX 503-678-5693 gksales@gkmachine.com · www.gkmachine.com