

# Pull Style Spreader

COMBINING TECHNOLOGY AND TRADITION SINCE 1976



GK Machine's stainless steel 120 cubic feet dry spreader is made of heavy duty steel components and is extremely durable for long lasting trouble-free spreading year after year.

With up to 60-foot spread widths, the adjustable spinner assembly allows quick and accurate settings for variable-rate applications, broadcasting materials farther and wider with consistent spread patterns.

The pull behind frame has a solid welded suspension, and features a tandem axle trailer with heavy duty 6-inch-wide conveyor chain. A RAVEN Encoder may be installed for adjustable chain speed with optional RAVEN 660 PWM.

Pressure-/flow-compensated hydraulics allows operators to maintain spread widths. With the dual spinners, operators can consistently place product throughout the field and prevent bottlenecking of product at row end.

The GK Pull Style Spreader is custom-built for a broad range of crops, and is extremely easy to set-up. The spreader comes with a variety of options to help you efficiently cover large fields fast. This spreader will become the operator's most valuable resource for quick and accurate fertilizer and mineral spreading.

- Low-maintenance design
- Pressure-/flow-compensated hydraulics
- Dual spinners for more spread control
- 304 stainless steel for corrosion resistance
- Heavy duty 6-inch conveyor chain



*Call for a friendly quote!*

**503-678-5525**

10590 Donald Road NE · Donald, Oregon 97020 FAX 503-678-5693 [gksales@gkmachine.com](mailto:gksales@gkmachine.com) · [www.gkmachine.com](http://www.gkmachine.com)

# Pull Style Spreader

COMBINING TECHNOLOGY AND TRADITION SINCE 1976



## Spreader Cart Specifications:

- Length 163¾"
- Width 72"
- Height 84¾"
- Tire size 12.5" x 15"

## Hopper Specifications:

- Stainless steel hull (304 stainless)
- 45" angle of sides
- 16.5 inches with 4 blades
- Length 97½"
- Width 72"
- Height 47½"
- Depth 40¾"
- Capacity 120 cubic feet (3 ton)  
or 80 cubic feet (2 ton)
- Spreading width 60 feet

## Conveyor Specifications:

- Heavy duty stainless steel 6-inch wide conveyor chain
- Press wheel driven conveyor easily engages or disengages with hydraulic cylinder
- RAVEN Encoder – adjustable speed control

## Frame and Suspension:

- Trailer length supports hull for better stability
- Tandem axle trailer for full support of dry box
- 6,000 lb. suspension spindles and hubs

## Options:

- Tongue extension
- Tarp kit
- Scale assembly
- Floating axles
- RAVEN SC600 in-cab controller (replaces GPS)
- Side Discharge Shoot



Call for a friendly quote!

**503-678-5525**

10590 Donald Road NE · Donald, Oregon 97020 FAX 503-678-5693 [gksales@gkmachine.com](mailto:gksales@gkmachine.com) · [www.gkmachine.com](http://www.gkmachine.com)