

# GK TR6 Track Sprayer

COMBINING TECHNOLOGY AND TRADITION SINCE 1976



## TR6 TRACK SPRAYER

The TR6 has the size, power, and capacity to cover large acres fast and efficiently. The new and improved TR6 has many new features that make this machine even more productive!

With a high tunnel clearance and on-the-go track width and height adjustment, it allows for easy straddling of multiple crop rows while carrying 400 gallons of product. The lightweight design along with the low ground pressure tracks get the TR6 out in the field long before the competition can even think about it.



The over-the-row spray delivery system with stainless steel saddle tanks, mechanical agitation, centrifugal or diaphragm pumps, product controllers, and a variety of boom configurations and sizes will meet all of your spraying needs. From wet drops and broadcast booms, to an air blast system and granular fertilizer spreaders – the TR6 is customizable to meet your specific crop needs.

Optional 3-point hitches allow the use of additional attachments: pre-pruners, hedgers, rotary mowers, trimmers and many other implements that can easily mount on the machine frame. The TR6 will make your operation more efficient, saving you time and money.



*Call for a friendly quote!*

**503-678-5525**

10590 Donald Road NE · Donald, Oregon 97020 FAX 503-678-5693 [gksales@gkmachine.com](mailto:gksales@gkmachine.com) · [www.gkmachine.com](http://www.gkmachine.com)

# GK TR6 Track Sprayer

COMBINING TECHNOLOGY AND TRADITION SINCE 1976



## STANDARD FEATURES

- Cummins 4.5L, Stage V, 173 HP, 576 lb-ft torque, increased fuel economy and quieter operation
- 2-speed planetary gearbox, 0 - 12.5 MPH
- Closed loop hydrostatic drive system
- Rubber track undercarriage with positive non-slip drive system
- Low ground pressure (5.5 – 7.5 PSI)
- Hydraulic “on-the-go” width and height adjustment
- Stainless steel pressurized cab with charcoal filtration
- Electronic steering with adjustable sensitivity and trim, capable of zero-radius turning
- Touch screen display console
- Integral joystick control
- LED lighting package
- Hydraulic 4 link implement lift with 54” of travel

## OPTIONAL FEATURES

- Hydraulic PTO – 36 gpm
- Reverse cab orientation
- Row pre-runners

- Hedgers/Pruners
- Cat II 3 point attachment (on each leg)
- Rotary mowers
- Quick-attach 4 link mount
- Custom equipment

## SPRAY SYSTEM

- Centrifugal or diaphragm (high pressure) pump
- Raven precision spray controller
- Conventional spray booms
- “Between-the-row” drop booms
- Air assist spray booms
- Granular (fertilizer) applicators

## DIMENSIONS

- Row centers: 80” - 120” or 96” - 136”
- Track width: 12” or 16”
- Track length: 120” (center to center)
- Ground clearance: 77” - 97”
- Machine length: 228” (with standard boom)
- Machine height: 146” (down position)
- Machine width: 126” (@ 96” centers, no booms)
- Machine weight: 14,800 lbs



Call for a friendly quote!

**503-678-5525**

10590 Donald Road NE · Donald, Oregon 97020 FAX 503-678-5693 [gksales@gkmachine.com](mailto:gksales@gkmachine.com) · [www.gkmachine.com](http://www.gkmachine.com)